Forward-Secure Sequential Aggregate Authentication (Short Paper)

Di Ma, Gene Tsudik University of California, Irvine {dma1, gts}@ics.uci.edu

Abstract

Wireless sensors are employed in a wide range of applications. One common feature of most sensor settings is the need to communicate sensed data to some collection point or sink. This communication can be direct (to a mobile collector) or indirect – via other sensors towards a remote sink. In either case, a sensor might not be able to communicate to a sink at will. Instead it collects data and waits (for a potentially long time) for a signal to upload accumulated data directly.

In a hostile setting, a sensor may be compromised and its post-compromise data can be manipulated. One important issue is forward security - how to ensure that precompromise data cannot be manipulated? Since a typical sensor is limited in storage and communication facilities, another issue is how to minimize resource consumption due to accumulated data. It turns out that current techniques are insufficient to address both challenges. To this end, we explore the notion of Forward-Secure Sequential Aggregate (FssAgg) authentication Schemes. We consider FssAgg authentication schemes in the contexts of both conventional and public key cryptography and construct a FssAgg MAC scheme and a FssAgg signature scheme, each suitable under different assumptions. This work represents the initial investigation of Forward-Secure Aggregation and, although the proposed schemes are not optimal, it opens a new direction for follow-on research.

KEYWORDS: sensors, signature schemes, authentication schemes, key compromise, forward security, aggregate signatures.

1 Introduction

Wireless sensors can enable large-scale data collection in many different settings, scenarios and applications. Examples abound in all kinds of tracking and monitoring applications in both civilian and military domains. A Wireless Sensor Network (WSN) might contain hundreds or thousands of low-cost sensors and one or more sinks or data collectors. Individual sensors obtain measurements from the environment and (periodically or upon request) forward the accumulated data to the sink. A sink might be a gateway to another network, a powerful data processing or storage center, or an access point for human interface. (Some WSNs support user-driven data queries and commands through the sink.)

In this paper, we are motivated by two types of envisaged sensor scenarios:

- A Sensors do not communicate with each other, i.e., there is *no sensor network* as such. Instead, a mobile device that we call a *collector*. A collector might not be fully trusted; it might be nothing more than an intermediary between sensors and an off-line (trusted) sink.
- **B** Sensors communicate but they do not actually "network", i.e., communication is restricted to mere forwarding of information from other sensors towards a sink or sinks. In this context, a sink is a fully trusted entity.

In either case, a sensor might not be able to communicate to a sink at will. Instead, it collects data and waits (potentially, for a long while) either for a signal – or some predetermined time – to upload accumulated data to a collector or a sink. Put another way, there is no real-time reporting of sensed information between sensors and a collector or a sink.

Data integrity and (sensor) authentication are essential security services required in most sensor applications [20] since sensors are often used in unattended and adversarial environments. They interact closely with the physical environment and with people, thus being subject to a wide range of security risks. An attacker may inject its own data as well as modify and delete data produced by sensors. As a result, sensor data must be authenticated before being processed and used for whatever purposes. Particularly in critical settings (e.g., radiation, seismic or intrusion monitoring) strong data integrity and authenticity guarantees are needed.

¹We use the terms "collector" and "sink" to distinguish between entities that gather data in the two scenarios.

Standard textbook techniques, such as MACs (Message Authentication Codes) or digital signatures, can be used in applications where data integrity/authenticity is required. However, several obstacles hinder straight-forward usage of these standard techniques.

One important issue is the threat of **sensor compromise** and the consequent exposure of secret keys used for MACs or signatures.² Key exposure makes it easy for the adversary to produce fraudulent data ostensibly sensed after the compromise. Moreover, it also allows the adversary to produce fraudulent data before the compromise, assuming it has not been reported to a sink or a collector. This is clearly undesirable. Fortunately, there are so-called forward-secure cryptographic techniques that allow the signer (sensor, in our case) to periodically evolve its secret key such that compromise of a current secret key cannot lead to compromise of secret key(s) used in past periods. It is therefore possible to mitigate the effects of sensor compromise by using a sense-and-sign approach. In other words, a sensor does not wait to sign (or MAC) ALL sensed data until it has to send it, since doing that would open all collected data to attack. Instead, it signs data as soon as it is sensed and evolves the signing key.

Another important issue is **storage and communication overheads**. Clearly, on-board storage is a limited commodity in most sensor settings and it is natural to minimize its size and consumption. In both scenarios A and B outlined above, a sensor gradually accumulates data (readings, measurements), stores it locally and – at some later time - sends it to a sink. We are not concerned in minimizing storage consumed by the actual data; that is an interesting topic in its own right. Instead, we are interested in minimizing storage due to authentication tags (i.e., MACs or signatures) since they represent pure overhead. If key compromise and forward security were not an issue, minimizing storage overhead would be trivial – a sensor simply signs or MACs all accumulated data once, before forwarding it to the sink. At the same time, forward security forces us to compute authentication tags per sensed unit of data, which we refer to as a message from now on.3 Therefore, a sensor accumulates as many authentication tags as messages while it waits for a time or a signal to off-load the data. This is problematic since even the size of a MAC (and certainly of a signature) can easily exceed the size of actual data, i.e., messages. At the minimum, each 128 bits per MAC or 160 bits per signature would need to be allocated.

Communication overhead is a related, though perhaps not as critical, matter. In scenario A, a sensor uploads accumulated messages directly to the collector. Thus, the communication overhead due to sending multiple authentication tags is less problematic than in Scenario B where the same overhead affects all sensors that forward information from other sensors towards the sink. (We refer to the oft-cited folklore in [3] which claims that wireless transmission of a single bit can consume over 1,000 times of the energy of a single 32-bit computation.)

Reconciling the need to minimize storage (and communication) overhead with the need to mitigate potential key compromise (i.e., obtain forward security) is precisely the topic of this paper.

Contributions: We explore Forward Secure Sequential Aggregate (FssAgg) authentication schemes that simultaneously mitigate the threat of key compromise and achieve optimal storage and communication efficiency. An FssAgg scheme allows a signer to combine multiple authentication tags generated in different key/time periods into a single constant-size tag. Compromise of the current key does not allow the attacker to forge any aggregate authentication tag containing elements pre-dating the compromise. Any insertion of new messages, modification and deletion (including truncation) of existing messages makes the aggregate tag demonstrably invalid. We consider this topic in both conventional and public key cryptographic settings and construct two practical schemes: an FssAgg MAC scheme as well as an FssAgg signature scheme.

Organization: After a brief overview of related work in Section 2, we introduce the model and security requirements in Section 3. Next, we present an *FssAgg* MAC scheme in Section 4 and an *FssAgg* signature scheme in 5. We give a brief performance evaluation of the *FssAgg* signature scheme in 6. Section 7 concludes the paper.

2 Related Work

NOTE: this section is kept brief due to dire space limitations.

The topic of this paper is quite distinct from data aggregation in sensor networks [8, 11, 12, 21, 22]. In an *FssAgg* authentication scheme, authentication objects are aggregate while data records (messages) are kept intact. In a data aggregation scheme, individual data information is lost and the aggregate value is used to provide or derive statistical information, such as mean, median or max/min. Data aggregation schemes are very useful, but unsuitable for applications, where the availability of individual sensed data records is required (e.g., temperature pattern sensing in a nuclear reactor).

The notion of forward security was introduced in the context of key-exchange protocols [10] and lagter adapted to signature schemes. Forward-secure signatures were first proposed by Anderson in [2] and subsequently formalized by Bellare and Miner in [4]. The main challenge is effi-

²Building an inexpensive tamper-proof, or even tamper-resistant, sensor is a much greater challenge.

³Note that the duration of the key evolvement period in a forwardsecure scheme does not have to match the time between successive sensor readings; however, to simplify the discussion, we assume that it does.

ciency: an ideal scheme must have constant (public and secret) key size, constant signature size as well as constant signing, verification, and (public and secret) key update operations. Several schemes proposed in the literature satisfy some or most of these requirements [1, 4, 13–15]. Also, in [5], Bellare and Yee examine forward security in the context of conventional cryptography.

Several aggregate signature schemes have been proposed in the literature, starting with the initial seminal result by Boneh, et al. [6, 16, 17]. An aggregate signature scheme combines k signatures generated by n signers ($k \geq n$) into a single and compact aggregate signature that, if verified, simultaneously verifies every component signature. Interestingly, our goal is to aggregate signatures by the *same* signer (e.g., a sensor), however, these signatures are computed in different periods, and with different keys. Thus, our goals impose no additional restrictions on existing definitions of aggregate signatures. Also, our envisaged schemes do not require simultaneous aggregaqtion of multiple signatures as in [6]; instead, we need sequential (incremental) aggregation as in [17] or [16].

3 Definitions and Properties

In this section we present some informal definitions and properties.⁴ An *FssAgg* signature scheme is composed of the following algorithms. They are quite similar to those in sequential aggregated signature schemes, notably, the recent scheme of Lu, et al. [16].

The key generation algorithm FssAgg.Kg is used to generate public/private key-pairs. Unlike the one used in [16], it also takes as input T – the maximum number of time periods (key evolvements).

The sign-and-aggregate algorithm *FssAgg.Asig* takes as input a private key, a message to be signed and a signature-so-far (an aggregated signature computed up to this point). It computes a new signature on the input message and combines it with the signature-so-far to produce a new aggregated signature. As the final step of *FssAgg.Asig*, it runs a key update subroutine *FssAgg.Upd* which takes as input the signing key for the current period and returns the new signing key for the next period (not exceeding *T*.) We make key update part of the sign-and-aggregate algorithm in order to obtain stronger security guarantees (see below).

The verify algorithm *FssAgg.Aver*, on input of a putative aggregate signature, a set of presumably signed distinct messages and a public key, outputs whether the aggregate is valid. (The distinction from non-forward-secure schemes is that we use a single public key, as there is only one signer.)

The key update algorithm *FssAgg.Upd* takes as input the signing key for the current period and returns the new sign-

ing key for the next period (provided that the current period does not exceed T-1.)

A secure *FssAgg* scheme must satisfy the following properties:

- 1. *Correctness:* Any aggregated signature produced with FssAgg.Asig must be accepted by FssAgg.Aver.
- 2. *Unforgeability:* Without the knowledge of any signing keys (for any period), no adversary can compute an aggregate signature on any message or set of messages.
- 3. Forward-security: No adversary who compromises the signer's i-th signing key can generate a valid aggregate signature containing a signed message for any period j < i except the aggregate-so-far signature generated by the signer before the compromise, i.e., the aggregated signature the adversary finds upon compromise.

Note that the last property subsumes security against truncation or deletion attacks. An adversary who compromises a signer has two choices: either it includes the intact aggregate-so-far signature in future aggregated signatures, or it ignores the aggregate-so-far signature completely and start a brand new aggregated signature. What it cannot do is selectively delete components of an already-generated aggregate signature.

4 A Forward-Secure Sequential Aggregate MAC Scheme

We now present a trivial *FssAgg* MAC scheme. It can be used to authenticate multiple messages when public (transferrable) verification is not required. As such, it is well-suited for scenario B in Section 1 where a sensor communicates (via other sensors) to the sink.

The scheme uses the following cryptographic primitives:

- \mathcal{H} : a collision resistant one-way hash function with domain restricted to k-bit strings: $\mathcal{H}: \{0,1\}^k \to \{0,1\}^k$.
- • H_a: a collision resistent one-way hash function with arbitrary length input:
 • H_a: {0,1}* → {0,1}^k.
- h: a secure MAC scheme $h: \{0,1\}^k \times \{0,1\}^* \to \{0,1\}^t$ that, on input of a k-bit key x and an arbitrary message m outputs a t-bit MAC $h_x(m)$.

FssAgg.Kg. Any symmetric key generation algorithm can be used to generate an initial k-bit secret key s. We set $sk_0 = vk = s$.

FssAgg.Asig. At time period i, the signer is given a message M_i to be signed and an aggregate-so-far MAC $\sigma_{1,i-1}$ on messages M_1, \dots, M_{i-1} . The signer first

⁴Our presentation is informal to conserve very limited space.

generates a MAC σ_i on M_i with h using sk_i : $\sigma_i = h_{sk_i}(M_i)$. It then computes $\sigma_{1,i}$ by folding σ_i onto $\sigma_{1,i-1}$ through \mathcal{H}_a : $\sigma_{1,i} = \mathcal{H}_a(\sigma_{1,i-1}||\sigma_i)$. \mathcal{H}_a acts as the aggregation function. Alternatively we can compute $\sigma_{1,i}$ as follows:⁵

$$\sigma_{1,i} = \mathcal{H}_a(\mathcal{H}_a(\cdots \mathcal{H}_a(\mathcal{H}_a(\sigma_1||\sigma_2)||\sigma_3))||\cdots)||\sigma_i)$$

where $\sigma_j = h_{sk_j}(M_j) \forall j = 1, \dots, i$. Finally, the signer executes the key update subroutine defined as:

FssAgg.Upd. We define the *i*-th signing key sk_i as the image under \mathcal{H} of the previous key sk_{i-1} : $sk_i = \mathcal{H}(sk_{i-1}), i > 0$. (This part is the same as the forward-secure MAC scheme in [20].)

FssAgg.Aver. To verify a candidate $\sigma_{1,i}$ over messages M_1, \dots, M_i , the verifier (who has the verifying key vk which is the same as the initial signing key sk_0) computes keys sk_1, \dots, sk_i through the public key update function. It then mimics the signing process and re-computes $\sigma_{1,i}^c$ and compares it with $\sigma_{1,i}$. If the two values match, it outputs valid. Otherwise it outputs invalid.

5 A Forward-Secure Sequential Aggregate Signature Scheme

If public (transferrable) verification is required we need a FssAgg signature scheme to check the authenticity of data records. Trivially, all aggregate signature schemes [6, 16, 17] can be used as a FssAgg signature scheme if we treat the key of signer i as the key used (by the same signer) in the time period i. However a trivial construction is useless for our purposes since a signer (e.g., a sensor) would need O(T) storage to store its secret keys.

The overall efficiency of a *FssAgg* signature scheme depends on the following metrics: 1) size of the aggregate signature; 2) size of the signing key; 3) complexity of key update; 4) complexity of aggregate signing; 5) size of verification key; 6) complexity of aggregate verifying. The first four represent *signer efficiency* and the last two represent *verifier efficiency*; the size parameters (aggregate signature,

signing key and verification key) represent *space efficiency* and the complexity parameters (sign, verify and key update) represent *time efficiency*. In our envisaged sensor scenarios, signer efficiency is much more important than verifier efficiency and space efficiency more important than time efficiency.

Focusing on the signer and space efficiency, we propose a *FssAgg* signature scheme based on the BLS signature scheme [6]. BLS signatures can be aggregated through EC multiplication by anyone [7]. We first introduce the BLS scheme and then show how to modify it to be a *FssAgg* signature scheme.

The BLS scheme works in groups with bilinear maps. A bilinear map is a map $e:G_1\times G_2\to G_T$, where: (a) G_1 and G_2 are two (multiplicative) cyclic groups of prime order q; (b) $|G_1|=|G_2|=|G_T|$; (c) g_1 is a generator of G_1 and g_2 is a generator of G_2 . The bilinear map $e:G_1\times G_2\to G_T$ satisfies the following properties:

- 1. Bilinear: for all $x \in G_1$, $y \in G_2$ and $a,b \in \mathbb{Z}$, $e(x^a,y^b)=e(x,y)^{ab}$;
- 2. Non-degenerate: $e(g_1, g_2) \neq 1$

The BLS scheme uses a full-domain hash function $\mathcal{H}_1(\cdot)$: $\{0,1\}^* \to G_1$. Key generation involves picking a random $x \in \mathbb{Z}_q$ for each signer, and computing $v=g_2^x$. The signer's public key is $v \in G_2$ and her secret key is x. Signing a message M involves computing the message hash $h = \mathcal{H}_1(M)$ and then the signature $\sigma = h^x$. To verify a signature one computes $h = \mathcal{H}_1(M)$ and checks that $e(\sigma, g_2) = e(h, v)$. The verification costs amount to 2 bilinear mappings.

To aggregate n BLS signatures, one computes the product of individual signatures as follows:

$$\sigma_{1,n} = \prod_{i=1}^{n} \sigma_i$$

where σ_i corresponds to the signature on message M_i . The aggregate signature $\sigma_{1,n}$ is of the same size as an individual BLS signature and aggregation can be performed incrementally and by anyone.

Verification of an aggregate BLS signature $\sigma_{1,n}$ includes computing the product of all message hashes and verifying the following match:

$$e(\sigma_{1,n}) \stackrel{?}{=} \prod_{i=1}^{n} e(h_i, v_i)$$

where v_i is the public key of the signer who generates σ_i on message M_i .

FssAgg.Kg The signer picks a random $x_0 \in \mathbb{Z}_p$ and computes a pair (x_i, v_i) $(i = 1, \cdots, T)$ as: $x_i = \mathcal{H}(x_{i-1})$, $v_i = g_2^{x_i}$. The initial signing key is x_0 and the public key is: $(v_1, \cdots, v_T) = (g_2^{x_1}, \cdots, g_2^{x_T})$.

Note that, in our sensor scenarios, a sensor (signer) would not generate its own keys. Instead, the sink

⁵Note that hash functions are generally designed as an iterative process [19]. That is, a hash function $\mathcal{H}: \{0,1\}^* \to \{0,1\}^k$ with arbitrarily long finite input is executed by iteratively invoking an internal (per block) function $f: \{0,1\}^{r+k} \to \{0,1\}^k$ (r>k as a hash function compresses its input) with fixed-size input. A hash input x of arbitrary finite length is divided into fixed-length r-bit blocks x_i . In each iteration, f takes on the current input block x_i and the intermediate result H_{i-1} produced by f in the previous iteration. We can thus modify the aggregation function as follows: form an input block with several MACs and then fold the block into the aggregate in one round. This way, $\sigma_{1,i}$ can be represented as: $\sigma_{1,i} = \mathcal{H}_a(\sigma_1||\sigma_2||\cdots||\sigma_i)$. Compared with 1, this aggregation function in is more efficient.

(or some other trusted party) would generate all public and secret keys for all sensors. The collector, however, would be given the public keys only.

FssAgg.Asig With inputs of message M_i to be signed, an aggregate-so-far signature $\sigma_{1,i-1}$ over messages M_1, \cdots, M_{i-1} and the current signing key x_i , the signer first computes a BLS signature on M_i using x_i : $\sigma_i = \mathcal{H}^{x_i}(index||M_i)$ where index denotes the position of M_i in the storage. The purpose of this index is to provide message ordering, since the original BGLS aggregation function does not impose any order on aggregate elements. Next, the signer aggregates σ_i onto $\sigma_{1,i-1}$ through multiplication: $\sigma_{1,i} = \sigma_{1,i-1} \cdot \sigma_i$. Finally, the signer updates the key.

FssAgg.Upd A signer evolves its secret signing key through the hash function \mathcal{H} : $x_i = \mathcal{H}(x_{i-1})$.

FssAgg.Aver The verifier uses Equation 1 and the public key pk to verify an aggregate signature $\sigma_{1,i}$

The security of our *FssAgg* signature scheme is based on the underlying BLS scheme and no other assumptions is needed. The following theorem summarizes the security of our *FssAgg* signature scheme and is strait-forward to prove. For a formal description of the security model and the proof of the theorem, please refer to [18].

Theorem 5.1 If BLS is a $(t', q_H, q_S', \epsilon)$ -secure signature scheme, our construction above is a $(t, q_H, q_S, T, \epsilon)$ -secure FssAgg signature scheme where $t' = t + O(q_H + q_S)$, $\epsilon' = \epsilon/T$, and $q_S' = q_S/T$.

A proof sketch for this theorem is presented in [18] which also contains the security model.

6 Performance

In this section, we evaluate the performance of the proposed BLS-based *FssAgg* signature scheme. We begin by accessing the cost in terms of basic cryptographic operations(e.g, multiplications, exponentiation, etc). Then we show the actual overhead incurred through experiment.

We use the notation in Table 1. We consider the generation and verification of a FssAgg signature $\sigma_{1,k*t}$ where t denotes the number of periods occupied by $\sigma_{1,k*t}$ and k denotes the number of signatures generated per time period. Table 2 illustrates the overhead (computation, storage and bandwidth) associated with the scheme in terms of cryptographic operations.

We used a field F_p where |p|=512 and we choose the size of group order as |q|=160. We test our scheme on a Pentium 1.86GHz machine with 512M memory in a Linux

Table 1. Notations.

$MtP^{\iota}(\mathcal{H}_{1}(\cdot))$	t map-to-point operations
$SclMult_m^t(l)$	t scalar multiplications with modulus
	of size m and exponent of size l
$SclAdd_{m}^{t}$	t scalar additions with modulus of size m
	t bilinear mappings
$Hash^t(l)(\mathcal{H}(\cdot))$	t hash operations with input size of l

Table 2. Operation Cost in Terms of Cryptographic Operations.

Parameters	Cost	Complexity
Signature Size	p	O(1)
Secret Key Size	q	O(1)
Key Update Time	Hash(q)	O(1)
Agg. Sign Time	$MtP^{1} + Exp^{1}_{ p }(q)$	O(1)
	$+Mult^{1}(p)$	
Public Key Size	T* q	O(T)
Agg Ver. Time	BM(t+1)+	O(t)
	$+Mult^{k*t-1}(p)$	

environment. The experiment result is listed in Table 3. Signature generation is quite efficient and it costs an average 7.64ms to generate a BLS signature (1.5ms on the map-to-point operation and 6.14ms on the scalar multiplication operation) and another 0.05ms to fold it into the aggregate. Aggregation imposes little overhead on the overall time for Asig. Verification cost is quite expensive because of the involvement of pairing operations. When the number of time periods increases to 100, it takes the verifier more than 2 seconds to verify. The verification cost might impose an upper ceiling on the total number of time periods T.

7 Summary and Future Work

In this paper we motivated the need for Forward-Secure Sequential Authentication to address both key exposure and storage efficiency issues. We constructed two sample Fs-sAgg schemes (one MAC-based and one signature-based). While our trivial MAC-based scheme is near-optimal in terms of efficiency, the signature-based scheme is not. Although it is both signer- and space-efficient, it is not verifier-friendly as the verifier needs O(T) space to store the public key and the verification is fairly expensive because of bilinear map operations. Constructing a more efficient scheme – with either (or both) compact public keys or lower verification complexity – is a challenge for future work. And, a more careful formal treatment of Forward-Secure Sequential Authentication is certainly needed.

Table 3. Operation Cost in msecs.

		BLS Sign		Aggregation	
Asig	1 signature	MtP^1	$SclMul_p^1(q)$	$SclAdd_p^1$	
		1.5	6.14	0.05	
	1 signature	53.62			
Aver	k=1000, t=1	54.40			
	k=100, t=10	295.71			
	k=10, t=100	2708.79			

References

- [1] M. Abdalla, and L. Reyzin. "A new forward-secure digital signature scheme." In *ASIACRYPT 2000*, pp. 116-129, 2000.
- [2] R. Anderson. "Two remarks on public-key cryptology Invited Lecture". Fourth ACM Conference on Computer and Communications Security, Apr. 1997.
- [3] K. Barr, and K. Asanovic. "Energy aware lossless data compression." In *Proc. of MobiSys'03*. San Francisco, CA, May 2003.
- [4] M. Bellare, and S. K. Miner. "A forward-secure digital signature scheme". In *Proc. of Adances in Cryptology Crypto 99*, LNCS Vol 1666:431-448, Aug. 1999.
- [5] M. Bellare, and B. Yee. "Forward-Security in Private-Key Cryptography". In Proceedings of CT-RSA'03, LNCS Vol. 2612, M. Joye ed, Springer-Verlag, 2003.
- [6] D. Boneh, B. Lynn, and H. Shacham. "Short signatures from the Weil pairing". J. Cryptology, 17(4):297-319, Sept. 2004. Extended abstract in Proceedings of Asiacrypt 2001.
- [7] D. Boneh, C. Gentry, B. Lynn, and H. Shacham. "Aggregate and verifiably encrypted signatures from bilinear maps". In *Proc. of Eurocrypt 2003*, LNCS 2656:416-432, May 2003.
- [8] C. Castelluccia, E. Mykletun, and G. Tsudik. "Efficient aggregation of encrypted data in wireless networks". In Mobile and Ubiquitous Systems: Networking and Services MobiQuitous 2005. July 2005.
- [9] Y. Frankel, P. Gemmell, P.D. MacKenzie, and M. Yung. "Optimal resilience proactive public-key cryptosystems". In *FOCS*, 1997.
- [10] C. G. Gunther. "An identity-based key-exchange protocol." *Advances in Cryptology EuroCrypt*'89. LNCS 434, pp. 29-37, 1990.

- [11] L. Hu, and D. Evans. "Secure aggregation for wireless networks." In *Workshop on Security and Assurance in Ad Hoc Networks*, 2003.
- [12] C. Intanagonwiwat, D. Estrin, R. Govindan, and J. Heidemann. "Impact of network density on data aggregation in wireless sensor networks". In *ICDCS'02*, pp. 457-458. 2002.
- [13] G. Itkis, and L. Reyzin. "Forward-secure signatures with optimal signing and verifying". In *Proc. of Ad*vances in Cryptology - Crypto'01, LNCS 2139:332-354, Aug. 2001.
- [14] A. Kozlov, and L. Reyzin. "Forward-secure signatures with fast key update". In *Prof. of the 3rd International Conference on Security in Communication Networks* (SCN'02), 2002.
- [15] H. Krawczyk. "Simple forwardsecure signatures from any signature scheme". In *Proc. 7th ACM Conference on Computer and Communication Security (CCS)*, pp. 108-115, Nov. 2000.
- [16] S. Lu, R. Ostrovsky, A. Sahai, H. Shacham, and B. Waters. "Sequential aggregate signatures and multisignatures without random oracles". In *Prof. of Eu*rocrypt 2006, May 2006.
- [17] A. Lysyanskaya, S. Micali, L. Reyzin, and H. Shacham. "Sequential aggregate signatures from trapdoor permutations." In *Proc. of Eurocrypt 2004*, LNCS 3027, pp. 245-254, Nov. 2001.
- [18] D. Ma, and G. Tsudik. "Forward-secure sequentical aggregate authentication". *IACR ePrint 2007/052*.
- [19] A. J. Menezes, P. C. van Oorschot, and S. A. Vanstone. "Handbook of applied cryptography". *CRC Press*, 1997. ISBN 0-8493-8523-7.
- [20] A. Perrig, J. Stankovic, and D. Wagner. "Security in wireless sensor networks". ACM Commun., 47(6):53-57, 2004.
- [21] D. Wagner. "Resilient aggregation in sensor networks". In Workshops on Security of Ad Hoc and Sensor Networks. 2004.
- [22] Y. Yang, X. Wang, S. Zhu, and G. Cao. "SDAP: a secure hop-by-hop data aggregation protocol for sensor networks". In *ACM MOBIHOC'06*. May 2006.