

# Quiz 6

To get credit for this quiz, use the Quiz tool at [eee.uci.edu](http://eee.uci.edu) to enter your answers, within the Sunday-to-Tuesday quiz period.

## Problem 1 (4 points)

(a) (4 points) A quiz has scores in the range 0 to 10. We can represent the distribution of scores on this quiz as a list of numbers, each number being the count of students who received a particular score. So in the list below, 1 person scored 0, 3 people scored 5, and 45 people scored 10:

```
counts = [1, 0, 0, 2, 2, 3, 8, 22, 33, 40, 45]
```

Suppose we want to print these statistics in a table in the following format:

```
0. 1 ( 0.64%)
1. 0 ( 0.00%)
2. 0 ( 0.00%)
3. 2 ( 1.28%)
4. 2 ( 1.28%)
5. 3 ( 1.92%)
6. 8 ( 5.13%)
7. 22 (14.10%)
8. 33 (21.15%)
9. 40 (25.64%)
10. 45 (28.85%)
```

In the following code, fill in each blank with one character so that the output is formatted as shown above.

```
TOPSCORE = 10
for s in range(TOPSCORE + 1):
    print("{:_____d}. {:3d} ({:_____ . _____}%)".format(s,
        counts[s], counts[s]/sum(counts)*100))
```

In the following code, fill in each blank with one character so that the output is formatted as shown above.

```
TOPSCORE = 10
for s in range(TOPSCORE + 1):
    print(f"{s:_____d}. {count[s]:3d} ({count[s]/sum(counts)*100:_____ . _____}%)")
```

(b) (4 points) Suppose we want to print a simple bar graph with the table of statistics:

```
0. 1 ( 0.64%) *
1. 0 ( 0.00%)
2. 0 ( 0.00%)
3. 2 ( 1.28%) **
4. 2 ( 1.28%) **
5. 3 ( 1.92%) ***
6. 8 ( 5.13%) *****
7. 22 (14.10%) *****
8. 33 (21.15%) *****
9. 40 (25.64%) *****
10. 45 (28.85%) *****
```

Rewrite the code above to produce the bar graph as shown.

**Problem 2** (10 points)

Suppose we wish to process text files that contain some "front matter"—lines at the start of the file that we wish to ignore, similarly to a part of this week's lab. Let's say that we have read the file into a list of strings, that the end of the front matter is indicated by a line in the file that says "END OF FRONT MATTER", and that we are guaranteed that this line will occur in the file.

Complete the definition of `remove_front_matter` below, consistent with its header, docstring, and assertions. [Recall that the annotation `[str]` means the same things as 'list of str'. Note that no actual file-handling commands are required for this solution.]

```
def remove_front_matter(linelist: [str]) -> [str]:  
    ''' Return input list with starting lines (through "END OF FRONT MATTER") removed  
    '''
```

```
test_list = ["To be skipped",  
            "Also to be skipped",  
            "END OF FRONT MATTER",  
            "To be included",  
            "Also to be included"]  
assert(remove_front_matter(test_list) == ["To be included",  
                                           "Also to be included"])  
assert(remove_front_matter(test_list[2:]) == ["To be included",  
                                              "Also to be included"])  
assert(remove_front_matter(test_list[:3]) == [ ])
```

**Problem 3** (6 points)

Complete the definition of `seconds_to_mmss` below, consistent with its header, docstring, and assertions. [Note: The integer division operator (`a//b`) gives the integer quotient of `a/b`. The mod operator (`%`) gives the remainder of `a/b`.] You do not have to worry about leading zeroes (like "11:05").

```
def seconds_to_mmss(seconds: int) -> str:
    ''' Convert a number of seconds to minutes and seconds in "mm:ss" format
    '''

    assert(seconds_to_mmss(15) == "0:15")
    assert(seconds_to_mmss(75) == "1:15")
    assert(seconds_to_mmss(3620) == "60:20")
```

**Problem 4** (10 points)

Parts of this excerpt from `help(str)` may be useful in this problem:

```
find(...)
    S.find(sub) -> int
    Return the lowest index in S where the string sub is found.
    Return -1 on failure.

split(...)
    S.split(sep) -> list of strings
    Return a list of the words in S, using sep as the delimiter string.

strip(...)
    S.strip() -> str
    Return a copy of the string S with leading and trailing whitespace removed.
```

Complete the function definition below, consistent with its header, docstring, and assertions.

```
MONTHS = ['January', 'February', 'March', 'April', 'May', 'June',
          'July', 'August', 'September', 'October', 'November', 'December']

def mmddyy_to_MonthDayYear(mmddyy: str) -> str:
    ''' From an argument in the form '10/31/152' (month, day, year),
        return a string in the form 'October 31, 2015'. Assume all
        values are valid numbers and all years are in this century
        (that means your function doesn't have to check).
    '''
```

```
assert(mmddyy_to_MonthDayYear('10/31/15') == 'October 31, 2015')
assert(mmddyy_to_MonthDayYear('12/1/07') == 'December 1, 2007')
assert(mmddyy_to_MonthDayYear('1/3/99') == 'January 3, 2099')
```

**Problem 5** (11 points)

Suppose we have a list of scores on a quiz, one score for each student, in the range 0 to 20. For example:

```
quiz_scores = [18, 20, 18, 20, 0, 10, 10, 20, 10, 20]
```

We would like to produce a list of counts, one count for each possible score

```
quiz_counts = [1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 3, 0, 0, 0, 0, 0, 0, 0, 2, 0, 4]
```

(a) (4 points) Write the function `zero_counts` that takes a number (such as the number of points on a quiz) and returns a list of zeros, one zero for each possible score).

```
def zero_counts (top_value: int) -> 'list of int':
    ''' Return a list of zeroes, with one zero for each possible score from zero to
        top_value
    '''
```

```
assert zero_counts(10) == [0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0]
assert zero_counts(0) == [0]
```

(b) (3 points) In one sentence, why does `zero_counts(10)` return a list of *eleven* zeroes?

(c) (4 points) Now, write the function `count_scores` that takes a list of scores and a number that represents the highest possible score; it returns a list of counts, indicating how many times each score occurred:

```
def count_scores(scores: 'list of int', top_score: int) -> 'list of int':
    ''' Return a list that tallies the number of times each value (from 0
        to top_score) occurs in the list of scores
    '''
```

```
assert count_scores([], 5) == [0, 0, 0, 0, 0, 0]
assert count_scores(quiz_scores, 20) == quiz_counts
```