

# A Privacy-Enabled Platform for COVID-19 Applications

Michael August\*\*, Christopher Davison<sup>+</sup>, Mamadou Diallo\*\*, Dhrubajyoti Ghosh\*, Peeyush Gupta\*, Christopher Graves\*\*, Shanshan Han\*, Michael Holstrom\*\*, Pramod Khargonekar\*, Megan Kline\*\*, Sharad Mehrotra\*, Shantanu Sharma\*, Nalini Venkatasubramanian\*, Guoxi Wang\*, Roberto Yus\*

\*University of California, Irvine, USA. <sup>+</sup>Ball State University, USA. \*\*Naval Information Warfare Center, Pacific, USA.

## ABSTRACT

We present our experiences in adapting and deploying TIPPERS<sup>1</sup>, a novel privacy-enabled IoT data collection and management system for smart spaces, to facilitate the monitoring of adherence to COVID-19 regulations in a university campus and a military facility.

## CCS CONCEPTS

• Information systems → Data management systems; • Security and privacy;

### ACM Reference Format:

Michael August\*\*, Christopher Davison<sup>+</sup>, Mamadou Diallo\*\*, Dhrubajyoti Ghosh\*, Peeyush Gupta\*, Christopher Graves\*\*, Shanshan Han\*, Michael Holstrom\*\*, Pramod Khargonekar\*, Megan Kline\*\*, and Sharad Mehrotra\*, Shantanu Sharma\*, Nalini Venkatasubramanian\*, Guoxi Wang\*, Roberto Yus\*. 2020. A Privacy-Enabled Platform for COVID-19 Applications. In *Proceedings of ACM Conference (Conference'17)*. ACM, New York, NY, USA, 2 pages. <https://doi.org/10.1145/nnnnnnn.nnnnnnn>

## 1 INTRODUCTION

As organizations reopen from mandatory lock-downs caused by the ongoing COVID-19 pandemic, regulations and policies have been formulated and put in place by federal, state, and local agencies to ensure adherence to public health guidelines - the key goal being to limit spread of the virus within organizational spaces. For instance, the states of Nevada and Louisiana mandated a maximum occupancy of 50% and 75%, respectively, for businesses (such as restaurants) that reopen. Other large organizations, including universities (e.g., UC Irvine) have defined custom policies, directives, and protocols to enable safe reopening of facilities for onsite work. These include regulations on physical distancing, building occupancy, hybrid in-class and online instruction; additional protocols for regular testing of staff and students and contact tracing have been established in concert with local public health authorities.

We describe a technology-based solution to help organizations monitor adherence to occupancy-based regulations, as well as, empower individuals to check for exposure to the virus within the organization's premises while still ensuring strong privacy properties. Our approach leverages TIPPERS [2], a novel general-purpose sensor data collection and management system for smart spaces, built over

<sup>1</sup><https://tippersweb.ics.uci.edu/covid19/d/IwAc1O9Wk/covid-19-effort-at-uc-irvine>

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than ACM must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from [permissions.acm.org](https://permissions.acm.org).

Conference'17, July 2017, Washington, DC, USA

© 2020 Association for Computing Machinery.

ACM ISBN 978-x-xxxx-xxxx-x/YY/MM... \$15.00

<https://doi.org/10.1145/nnnnnnn.nnnnnnn>

the past five years. A bedrock principle that serves as the core foundation of TIPPERS is **privacy by design**. In TIPPERS, data collected from sensors is subject to strict privacy policies that exploit a range of privacy enhancing technologies ranging from device-id randomization, encryption, to differential privacy. In the following, we first provide a brief introduction to TIPPERS, followed by a description of two deployments of TIPPERS with applications related to COVID-19.

## 2 TIPPERS

TIPPERS creates an abstraction of the underlying sensor infrastructure by translating between the world of IoT devices (i.e., sensors, actuators, raw observations, etc.) and the world where people act (i.e., interactions of people, and spaces, phenomena, etc.). The system is based on a domain model that represents both these layers (devices, applications) and enables users/developers to interact with high-level semantically meaningful concepts. It also includes ontology-based translation algorithms to convert user requests at the high-level, (e.g. *retrieve spaces where occupancy is higher than 20% of capacity*) into actions on the specific underlying device infrastructure. TIPPERS, thus simplifies the development of smart applications and facilitates portability as applications are built on high-level semantic concepts, not at the device level. Furthermore, the semantic view simplifies the definition of privacy policies allowing users to express what they want to protect, e.g., *do not capture my location when I am with John in a private space during working hours*. TIPPERS uses such privacy policies to constrain and guide its data collection, storage, and sharing practices.

The TIPPERS system incorporates *virtual sensors*, wherein streams of sensor data can be used to create streams of inferences. For instance, a virtual sensor can translate connectivity data (e.g., connectivity logs from WiFi access points (APs)) into occupancy of different spaces over time. A key component of the TIPPERS architecture is the *mediation module* that appropriately stores sensor data into one or more underlying database/storage technologies (e.g., allowing the use of multiple database platforms). Mediation enables TIPPERS to store data in different systems based on the characteristics of the data, its security requirements, and the type of queries that need to be executed. In particular, TIPPERS stores sensitive data in secure databases (supporting encrypted representation) and the mediator automatically transforms TIPPERS queries to execute on such databases.

## 3 COVID-19 MONITORING DEPLOYMENTS

TIPPERS can be used in multiple scenarios as it has a generic implementation and is capable of collecting/processing/analyzing data from various types of sensors. Furthermore, TIPPERS provides abstraction and easy-to-use REST APIs to developers for rapid application development. Below we describe two TIPPERS deployment with different setup and applications (see Figure 1).




Figure 1: Deployments of TIPPERS.

### 3.1 UCI Campus

UCI campus has a large scale campus-wide deployment of TIPPERS, where it provides a variety of location-based services based on exploiting WiFi connectivity events from personal devices carried by individuals captured by the campus network. Such events are of the form (MAC address, time stamp, wap) that correspond to the MAC of connected device, the timestamp when the connection occurred and the WiFi AP (wap) to which the device is connected. Since APs are at fixed locations, connectivity events can be used to locate a device to be in the region covered by the AP. TIPPERS include ML code to locate individuals to finer (e.g., room level) granularity [1]. Location data, appropriately encrypted, is used to build several applications to help the UCI community with COVID-19.

**Occupancy adherence** that assesses if the community is indeed implementing occupancy and social distancing advisories suggested by the campus administration. Specifically, as shown in Figure 1<sup>2</sup>, we illustrate the ability to monitor when regions such as classrooms, meeting spaces and shared offices exceed desired occupancy levels, identify locations within the organization where there has been a high rate of people passing by and hotspots where groups of individuals tend to congregate. Such monitoring allows organizations to conduct an in-depth analysis to reveal potential exposure hotspots, inject interventions (dispatching supervisors who can nudge individuals to relocate) or make remedial operational changes such as scheduling more-frequent sanitization where needed. TIPPERS includes data cleaning algorithms to account for multiple devices carried by individuals (that would result in over-counting), as well as, sporadic and noisy nature of the WiFi connectivity data in computing occupancy. **Exposure Tracing** that enables individuals to share information (without revealing their identity) to empower TIPPERS to determine location (and time) when those individuals were in the region. Exposure tracing helps identify regions at the organization’s premises where exposure by others to those infected could have occurred. It also includes mechanism for individuals to check (again, without revealing identity) if they were overlapped with an infected individual in a region. Exposure tracing are extremely useful to help focus and target contact tracing efforts, that are often time-consuming by rapidly and accurately determining those who potentially may have come in contact with an infected individual.

<sup>2</sup>The figure also shows a table with the spaces that do not adhere to the social distance criteria in red.

### 3.2 Naval Base San Diego

In this demonstration deployment at the Naval Base San Diego (NBSD)<sup>3</sup> (see the bottom of Figure 1), the goal was to use TIPPERS to perform more fine-grained tracking of people. The space, a pier at NBSD, was smaller than the previous use case and was highly instrumented with WiFi APs, Bluetooth beacons, RFID readers, and smartphones with a TIPPERS client application (capturing GPS readings among others). While privacy was not as big of a constraint wrt the deployment at UCI, the challenge in this deployment was that of fusing sensor data to accurately locate individuals in a robust manner. Requirements about social distancing (in terms of number of meters between people) had to be fulfilled.

The experiments performed (tailored towards COVID-19 mitigation) involved 30 Navy personnel, who served as participants, and performed a series of scenarios as they moved between different zones on the pier. Data was passively captured using the WiFi infrastructure and actively using the TIPPERS client application on the smartphones. Then, the data was correlated by TIPPERS to locate individuals in the different zones of the pier (each zone had been defined in the system to cover a small area). In this process, ML software components in the system were used to triangulate the location of a person given the signal obtained from the Bluetooth beacons and WiFi APs when GPS data was unavailable. Finally, the information of multiple individuals had to be correlated to check whether social distancing criteria were met.

TIPPERS demonstrated the ability to correlate and display tracking data in near-real-time, exhibiting its potential for use in COVID-19 applications such as: **Quarantine zone verification and access restrictions**, which monitor which areas have been visited by infected individuals and alerted when an infected individual visited a safe location and **Verified “secure bubble” transfer**, in which a unit (e.g., a group of individuals) have to be protected and alerts have to be triggered if any of its members came in contact with an infected individual. In the experiments, the system presented high accuracy and robustness to different scenarios thanks to the number of sensors deployed and the internal algorithms to correlate their captured data.

## 4 CONCLUSIONS

Our efforts in adapting TIPPERS to support COVID-19 applications has met with significant interest both within UCI campus and the US Navy<sup>4</sup>. TIPPERS occupancy apps are in operational use in 4 buildings as part of the reopening strategy. Given TIPPERS support for semantic abstraction, sensor-agnostic, general purpose design, and support for privacy technologies, adopting it to COVID-19 applications was relatively straightforward: mainly requiring writing simple SQL queries and GUIs to display results. We are currently working with various stakeholders to support the specific needs of different types of buildings and spaces both at UCI and at other organizations that are planning to adopt the system.

## REFERENCES

- [1] Yiming Lin et al. 2020. LOCATER: Cleaning WiFi Connectivity Datasets for Semantic Localization. *CoRR* abs/2004.09676 (2020).
- [2] Sharad Mehrotra et al. 2016. TIPPERS: A privacy cognizant IoT environment. In *PerCom Workshops*. 1–6.

<sup>3</sup><https://www.dvidshub.net/news/374318/navwar-trident-warrior-team-assesses-new-tracking-technology-covid-19-mitigation>

<sup>4</sup><https://tippersweb.ics.uci.edu/highlights>